


## Model Type R



### SPECIFICATIONS



R-2

R panel radiators are manufactured in the USA from cold rolled steel. The panels are finished in gloss powdercoat and available in many standard colors and over 100 optional colors. These panels are made in lengths from 2'-0" to 29'-6", and heights from 3" to 70". Standard piping connections are 1/2" NPT for inlet and outlet piping, and 1/8" NPT for vents (3/4" NPT inlets and outlets are available by special order). For more complete R specifications, please refer to the Runtal technical pages.

### BTUH/FT RATINGS

Energy efficient as well as space saving, R panels are the most radiant of the Runtal line. These panels provide more comfort at a lower room temperature than convective heaters. Various average water temperatures (AWT) are shown here for convenience, but for more specific conditions use the appropriate correction factor with the 215°F rating. Please see the technical pages for the correction factor best suited to the design conditions.

BTUH/ft Ratings @ 65°F EAT					
MODEL	HEIGHT inches	DEPTH inches	215°F	180°F	140°F
R-1	2.8	1.6	230	160	90
R-2	5.7	1.6	420	300	170
R-3	8.6	1.6	620	440	250
R-4	11.5	1.6	820	580	330
R-5	14.4	1.6	1020	720	410
R-6	17.3	1.6	1220	860	500
R-7	20.2	1.6	1430	1010	580
R-8	23.1	1.6	1640	1160	660
R-9	26.0	1.6	1850	1300	750
R-10	29.0	1.6	2060	1450	830

### MOUNTING SYSTEMS



R-4

Wall mounting with a continuous mounting system (brackets included) is standard on all R panels. Free standing, recessed wall, and curved panel mounting systems are also available. Please see the R technical pages for more complete mounting details.