


ThermoTouch



SPECIFICATIONS



TT-3

Runtal ThermoTouch® (TT) panel radiators are designed for low surface temperature applications such as schools and hospitals. The panels are finished in a gloss powdercoat, and are available in many standard colors and over 100 optional colors. These panels are made in lengths from 2'-0" to 29'-6", and heights from 6" to 12". Standard piping connections are 1/2" NPT for inlet and outlet piping, and 1/8" NPT for vents (3/4" NPT inlets and outlets are available by special order). For more complete TT specifications, please refer to the Runtal technical pages.

BTUH/FT RATINGS

Energy efficient as well as space saving, TT panels are both radiant and convective. These panels provide more comfort at a lower room temperature than convective heaters. Various average water temperatures (AWT) are shown here for convenience, but for more specific conditions use the appropriate correction factor with the 215°F rating. Please see the technical pages for the correction factor best suited to the design conditions.

BTUH/ft Ratings @ 65°F EAT					
MODEL	HEIGHT inches	DEPTH inches	215°F	180°F	140°F
TT-2	6.0	3.3	870	610	349
TT-3	9.0	3.3	1120	784	451
TT-4	12.0	3.3	1360	952	544

MOUNTING SYSTEMS



TT-3

Wall mounting with a continuous mounting system (brackets included) is standard on all TT panels. Please see the TT technical pages for more complete mounting details.